

Washer extractors

High Spin washer extractors TP

HIGH SPIN WASHER EXTRACTOR, LA-18 TP E

DIMENSIONS		Article	Packed
Length	mm	**884,00**	**930,00**
Depth	mm	**914,00**	**1.030,00**
Height	mm	**1.409,00**	**1.700,00**
Weigth	Kg	**360,00**	**393,00**
Volumen	m3		**1,63**

ELECTRICITY		
Electric power	KW	**12,75**
230V -1+N		**OPC2x25+T-100A**
230V - III		**3x10+T -63 A**
400V - III+N		**4x4+T - 32 A**

WATER	
Water consumption (lit/h)	**218,00**
Pressure (Kg/cm2)	**2 - 4**

GAS

Not used

STEAM Not used

AIR Not used

LEVEL SOUND (dB) **60,00**

HIGH SPIN WASHER EXTRACTOR, LA-18 TP E
Made of stainless steel.
Capacity: 20 kg (1:9) or 18 kg (1:10).
Microprocessor “Touch Plus Control” with display.
26 pre-set programs (4 economic programs).
Possibility of programming, export and import programs through USB memory, without limite.
“WASH CONTROL” management software included.
Digital sequence display.
8 signals for automatic liquid dosing, programmable in time and delay.
Possibility to install an automatic detergent doser on the rear of the machine.
Detergent dispenser with 4 compartments (pre-wash, wash, bleachers and softeners).
Water levels completely modifiable.
3 water inlets (Hot water, Cold water, Soft water).
WET CLEANING SYSTEM:
-Water levels completely modifiable.
-Possible manual dosing for evey 8 signals during the cycle.
-Minimum washing speed: 15 r.p.m.
-Minimum thythm ON-OF: 1 second.
Safety switch for door opening.
Wash and spin speeds are configurable.
These machines have electronic control of imbalance with frequency variator, that detects the load uncentered before spinning.
No need to be fixed to the floor.
Drum diameter: 700 mm.
Deepth drum: 470 mm.
Door diameter: 373 mm.
Spin speed: 1.080 r.p.m.
G Factor: 450.
Easy to attach automatic dosser dispenser at rear of machine.
Water consumption in program nº 2 60º: 218 litres.
Heating system: Electric.
Elements heating power: 12 kW.
Total power: 12,75 kW.
Dimensions: 884 x 913 x 1.409 mm

Connections points	**X**	**Y**	**Z**	**Diameter**	**Information**
ELECTRICITY	109	0	1.129		0
DRAIN	347	0	99	3"	
SOFT COLD WATER	437	0	1.331	3/4"	
COLD WATER	810	0	1.331	3/4"	
HOT WATER	517	0	1.331	3/4"	

