

**Washer extractors**

**High Spin washer extractors TP**

# HIGH SPIN WASHER EXTRACTOR, LA-11 TP E

| **DIMENSIONS** | | Article | Packed |
|---|---|---|---|
| Length | mm | **692,00** | **730,00** |
| Depth | mm | **788,00** | **1.000,00** |
| Height | mm | **1.158,00** | **1.410,00** |
| Weigth | Kg | **230,00** | **239,00** |
| Volumen | m3 | | **1,03** |

| **ELECTRICITY** | | |
|---|---|---|
| Electric power | KW | **6,25** |
| 230V -1+N | | **2x10+T-32 A** |
| 230V - III | | **3x4+T - 32 A** |
| 400V - III+N | | **4x1,5+T - 16 A** |

| **WATER** | |
|---|---|
| Water consumption (lit/h) | **135,00** |
| Pressure (Kg/cm2) | **2 - 4** |

**GAS**

Not used

**STEAM** Not used

**AIR** Not used

**LEVEL SOUND** (dB) **60,00**

HIGH SPIN WASHER EXTRACTOR, LA-11 TP E
Made of stainless steel.
Capacity: 11 kg (1:9) or 10 kg (1:10).
Microprocessor “Touch Plus Control” with display.
26 pre-set programs (4 economic programs).
Possibility of programming, export and import programs through USB memory, without limite.
“WASH CONTROL” management software included.
Digital sequence display.
8 signals for automatic liquid dosing, programmable in time and delay.
Possibility to install an automatic detergent doser on the rear of the machine.
Detergent dispenser with 4 compartments (pre-wash, wash, bleachers and softeners).
Water levels completely modifiable.
3 water inlets (Hot water, Cold water, Soft water).
WET CLEANING SYSTEM:
-Water levels completely modifiable.
-Possible manual dosing for evey 8 signals during the cycle.
-Minimum washing speed: 15 r.p.m.
-Minimum thythm ON-OF: 1 second.
Safety switch for door opening.
Wash and spin speeds are configurable.
These machines have electronic control of imbalance with frequency variator, that detects the load uncentered before spinning.
No need to be fixed to the floor.
Drum diameter: 532 mm.
Deepth drum: 425 mm.
Door diameter: 290 mm.
Spin speed: 1.245 r.p.m.
G Factor: 450.
Easy to attach automatic dosser dispenser at rear of machine.
Water consumption in program nº 2 60º: 135 litres.
Heating system: Electric.
Elements heating power: 6 kW.
Total power: 6,25 kW.
Dimensions: 692 x 788 x 1.158 mm

| Connections points | X | Y | Z | Diameter | Information |
|---|---|---|---|---|---|
| ELECTRICITY | 106 | 0 | 871 | | 0 |
| SOFT COLD WATER | 413 | 0 | 1.050 | 3/4" | |
| DRAIN | 252 | 0 | 93 | 3" | |
| COLD WATER | 623 | 0 | 1.070 | 3/4" | |
| HOT WATER | 468 | 0 | 1.050 | 3/4" | |

