

Washer extractors

Fast Spin washer extractors TP

FAST SPIN WASHER, LR-14 TP E

DIMENSIONS		Article	Packed
Length	mm	**719,00**	**800,00**
Depth	mm	**810,00**	**990,00**
Height	mm	**1.158,00**	**1.350,00**
Weigth	Kg	**239,00**	**247,00**
Volumen	m3		**1,07**

ELECTRICITY		
Electric power	KW	**9,50**
230V -1+N		**OPC2x16+T-63 A**
230V - III		**3x6+T - 40 A**
400V - III+N		**4x2,5+T - 25 A**

WATER	
Water consumption (lit/h)	**168,00**
Pressure (Kg/cm2)	**2 - 4**

GAS

Not used

STEAM Not used

AIR Not used

LEVEL SOUND (dB) **60,00**

FAST SPIN WASHER EXTRACTOR, LR-14 TP E
Made of stainless steel.
Capacity: 14 kg (1:9) or 13 kg (1:10).
Microprocessor “Touch Plus Control” with display.
26 pre-set programs (4 economic programs).
Possibility of programming, export and import programs through USB memory, without limite.
“WASH CONTROL” management software included.
Digital sequence display.
8 signals for automatic liquid dosing, programmable in time and delay.
Possibility to install an automatic detergent doser on the rear of the machine.
Detergent dispenser with 4 compartments (pre-wash, wash, bleachers and softeners).
Water levels completely modifiable.
3 water inlets (Hot water, Cold water, Soft water).
WET CLEANING SYSTEM:
- -Water levels completely modifiable.
- -Possible manual dosing for evey 8 signals during the cycle.
- -Minimum washing speed: 15 r.p.m.
- -Minimum thythm ON-OF: 1 second.

Safety switch for door opening.
Wash and spin speeds are configurable.
These machines have electronic control of imbalance with frequency variator, that detects the load uncentered before spinning.
Hard mounted machine. Machine must be fixed to the floor. Elements not included
Drum diameter: 620 mm.
Deepth drum: 430 mm.
Door diameter: 373 mm.
Spin speed: 760 r.p.m.
G Factor: 200.
Easy to attach automatic dosser dispenser at rear of machine.
Water consumption in program nº 2 60º: 135 litres.
Heating system: Electric.
Elements heating power: 9 kW.
Total power: 9,50 kW.
Dimensions: 719 x 810 x 1.158 mm

Connections points	**X**	**Y**	**Z**	**Diameter**	**Information**
ELECTRICITY	108	0	1.022		0
SOFT COLD WATER	440	0	1.196	3/4"	
DRAIN	252	0	80	3"	
COLD WATER	650	0	1.216	3/4"	
HOT WATER	495	0	1.196	3/4"	

