

Tumble Dryers

Tumble Dryers Green Evolution

TUMBLE DRYER, SR-16 E

DIMENSIONS		Article	Packed
Length	mm	**785,00**	**880,00**
Depth	mm	**1.100,00**	**1.225,00**
Height	mm	**1.694,00**	**1.840,00**
Weigth	Kg	**190,00**	**225,00**
Volumen	m3		**1,98**

ELECTRICITY		
Electric power	KW	**18,55**
230V -1+N		**NO**
230V - III		**3x16+T - 80 A**
400V - III+N		**4x6+T - 50 A**

WATER

Not used

GAS

Not used

STEAM Not used

AIR Not used

LEVEL SOUND (dB) **64,00**

TUMBLE DRYER, SR-16 E GREEN EVOLUTION
Load Capacity : 18 kg. (load factor 1:18) and 15 kg (load factor 1:22).
Production: ÷ 33 kg/h.
External case made of skin plate, grey color, with stainless steel aesthetics.
Axial-radial airflow gives low energy consumption and a bigger drying efficiency.
Time selector.
Temperature selector.
COOL DOWN at end of cycle.
Push -Pull button to START/STOP.
Lamp indicator ON and HEATING.
Open door with safety device.
EMERGENCY stop.
Frecuency speed variator.
Alarm noise indicator at end of cycle.
Air extraction volume: 870 m3/h.
IMPORTANT: Stainless steel drum.
IMPORTANT: Reversing drum .
Drum diameter: 750 mm
Depth of drum: 746 mm
Diameter of door: 574 mm.
reversible door hanging.
Fluff filter in lower part .
Transmission by means of motoreducer.
Main heating system: electric
Electrical connection : 400 V - III+N+ GROUND - 50/60 Hz.
Heating power: 18 kW
Total power: 18,55 kW.
Dimensions: 785 x 1.110 x 1.694 mm

OPTIONS:
- Door with double glass
- External case in stainless steel
- Front panel in stainless steel
- Marine version for ships (440 V III)

Connections points	**X**	**Y**	**Z**	**Diameter**	**Information**
ELECTRICITY	528	0	821		0
EXHAUST	558	0	169	200 mm.	

