

Tumble Dryers

Tumble Dryers Green Evolution

TUMBLE DRYER, SR-23 E

DIMENSIONS		Article	Packed
Length	mm	**890,00**	**960,00**
Depth	mm	**1.345,00**	**1.430,00**
Height	mm	**1.812,00**	**1.930,00**
Weigth	Kg	**338,00**	**370,00**
Volumen	m3		**2,64**

ELECTRICITY		
Electric power	KW	**24,67**
230V -1+N		**NO**
230V - III		**3x25+T-125 A**
400V - III+N		**4x10+T - 63 A**

WATER

Not used

GAS

Not used

STEAM Not used

AIR Not used

LEVEL SOUND (dB) **64,00**

TUMBLE DRYER, SR-23 E GREEN EVOLUTION
Load Capacity : 25 kg. (load factor 1:18) or 21 kg (load factor 1:22).
Production: ÷ 46 kg/h.
External case made of skin plate, grey color, with stainless steel aesthetics.
Axial-radial airflow gives low energy consumption and a bigger drying efficiency.
Time selector.
Temperature selector.
COOL DOWN at end of cycle.
Push -Pull button to START/STOP.
Lamp indicator ON and HEATING.
Open door with safety device.
EMERGENCY stop.
Frecuency speed variator.
Alarm noise indicator at end of cycle.
Air extraction volume: 1500 m3/h.
IMPORTANT: Stainless steel drum.
IMPORTANT: Reversing drum .
Drum diameter: 855 mm
Depth of drum: 905 mm
Diameter of door: 574 mm.
reversible door hanging.
Fluff filter in lower part .
Transmission by means of motoreducer.
Main heating system: electric
Electrical connection : 400 V - III+N - 50/60 Hz.
Heating power: 24 kW
Total power: 24,67 kW.
Dimensions: 890 x 1.245 x 1.812 mm

OPTIONS:
- Humidity sensor with intelligent drying
- Door with double glass
- External case in stainless steel
- Front panel in stainless steel
- Marine version for ships (440 V III)

Connections points	**X**	**Y**	**Z**	**Diameter**	**Information**
ELECTRICITY	637	0	861		0
EXHAUST	663	0	174	200 mm.	

