

Tumble Dryers

Tumble Dryers Green Evolution

TUMBLE DRYER, SR-28 E

DIMENSIONS		Article	Packed
Length	mm	**985,00**	**1.090,00**
Depth	mm	**1.054,00**	**1.150,00**
Height	mm	**1.946,00**	**2.105,00**
Weigth	Kg	**350,00**	**390,00**
Volumen	m3		**3,10**

ELECTRICITY		
Electric power	KW	**31,15**
230V -1+N		**NO**
230V - III		**3x70+T - 180 A**
400V - III+N		**4x25+T - 125 A**

WATER

Not used

GAS

Not used

STEAM Not used

AIR Not used

LEVEL SOUND (dB) **66,00**

TUMBLE DRYER, SR-28 E GREEN EVOLUTION
Load Capacity : 31 kg. (load factor 1:18) or 25 kg (load factor 1:22).
Production: ÷ 55 kg/h.
External case made of skin plate, grey color, with stainless steel aesthetics.
Axial-radial airflow gives low energy consumption and a bigger drying efficiency.
Time selector.
Temperature selector.
COOL DOWN at end of cycle.
Push -Pull button to START/STOP.
Lamp indicator ON and HEATING.
Open door with safety device.
EMERGENCY stop button.
Frecuency speed variator.
Alarm noise indicator at end of cycle.
Air extraction volume: 1500 m3/h.
IMPORTANT: Stainless steel drum.
IMPORTANT: Reversing drum.
Reversing system of the drum.
Drum capacity: 550 litres.
Diameter of door: 802 mm.
Fluff filter in lower part .
Transmission by means of pulleys.
Main heating system: electric.
Electrical connection : 400 V - III+N - 50/60 Hz.
Heating power: 30 kW
Total power: 31,15 kW.
Dimensions: 985 x 1.054 x 1.946 mm

OPTIONS:
- Door with double glass
- External case in stainless steel
- Front panel in stainless steel
- Marine version for ships (440 V III)

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	205	0	1.490		
EXHAUST	744	0	167	200 mm.	

