Electrolux

Modular Cooking Range Line thermaline 85 - 2-Burner Gas Top with Ecoflam, 1 Side, Backsplash

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



Modular Cooking Range Line

thermaline 85 - 2-Burner Gas Top with Ecoflam, 1 Side, Backsplash

588527 (MBGCBBDOPI)	2-burner gas top, ecoflam, one-side operated with backsplash

Short Form Specification

Item No. _____

Unit constructed according to DIN 18860_2 with 20 mm drop nose top. Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304). 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. 2 gas burners with optimized combustion, flame failure device, thermocouple safety hand valve and protected pilot flame. Triple ring "flower" flame burners with anti-clogging design. Manual gas valves allow precise flame intensity control. Large pan support in cast iron with long center fins for various pan sizes. ECOFLAM pan detection system to save energy and to reduce unnecessary heat radiation in the kitchen. Deep flat spillage tray with rounded corners and drain hole. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.
IPX4 water resistant certification.
Configuration: One side operated top with backsplash. The base needs to be supplied by the factory. Please include appropriate base.

APPROVAL: _____

Main Features

- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- Large sized pan support in cast iron with long center fins to allow the use of the largest down to the smallest pans.
- Manual gas valves allow precise control of the flame intensity between high and low positions.
- Pans can easily be moved from one area to another without lifting.
- IPX4 water resistance certification.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic silicon "soft" grip for easier handling and cleaning. The special design of the controls prevent infiltration of liquids or soil into vital components.
- Burners with optimized combustion. Triple ring flower flame burners with anti-clogging design.
- Deep flat spillage tray with rounded corners and drain hole to facilitate cleaning.
- Model is supplied with Ecoflam pan detection system, which reduces energy consumption and unnecessary heat dispersion in the kitchen.

Construction

- Each burner equipped with thermocouple safety hand valve and protected pilot flame.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top.

Optional Accessories

• Connecting rail kit for appliances with backsplash, 850mm	PNC 912498 ❑
• Portioning shelf, 400mm width	PNC 912522 ❑
• Portioning shelf, 400mm width	PNC 912552 ❑
• Folding shelf, 300x850mm	PNC 912579 ❑
• Folding shelf, 400x850mm	PNC 912580 ❑
• Fixed side shelf, 200x850mm	PNC 912586 ❑
• Fixed side shelf, 300x850mm	PNC 912587 ❑
• Fixed side shelf, 400x850mm	PNC 912588 ❑

Electrolux


Modular Cooking Range Line
thermaline 85 - 2-Burner Gas Top with Ecoflam, 1 Side, Backsplash

- Connecting rail kit for appliances with backsplash: modular 85 (on the left) to ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right) PNC 912979 ❑
- Connecting rail kit for appliances with backsplash: modular 85 (on the right) to ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left) PNC 912980 ❑
- Back panel, 400x700mm, for units with backsplash PNC 913009 ❑
- Endrail kit, flush-fitting, with backsplash, left PNC 913115 ❑
- Endrail kit, flush-fitting, with backsplash, right PNC 913116 ❑
- Endrail kit (12.5mm) for thermaline 85 units with backsplash, left PNC 913206 ❑
- Endrail kit (12.5mm) for thermaline 85 units with backsplash, right PNC 913207 ❑
- U-clamping rail for back-to-back installations with backsplash PNC 913226 ❑
- Insert profile, d=850mm PNC 913231 ❑
- Kit LPG nozzles for 2 burner (7 kW) gas 30/31 PNC 913285 ❑
- TL85 GAS - WALL MOUNT. KIT 400X850X400 PNC 913610 ❑
- Stainless steel side panel (12,5mm), 850x400mm, left side, wall mounted PNC 913632 ❑
- Stainless steel side panel (12,5mm), 850x400mm, right side, wall mounted PNC 913633 ❑
- Stainless steel side panel (12,5mm), 850x400mm, flush-fitting, left side, wall mounted PNC 913634 ❑
- Stainless steel side panel (12,5mm), 850x400mm, flush-fitting, right side, wall mounted PNC 913635 ❑


The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Modular Cooking Range Line thermaline 85 - 2-Burner Gas Top with Ecoflam, 1 Side, Backsplash

Front




Top



EQ = Equipotential screw
G = Gas connection

Side



Gas

Gas Power:	
588527 (MBGCBBDOPI)	47726 Btu/hr (14 kW)
Gas Type Option:	
Gas Inlet:	1/2"

Key Information:

Configuration:	One-Side Operated;Top
Front Burners Power:	7 - kW
Back Burners Power:	7 - 0 kW
Back Burners Dimension - mm	Ø 70
Front Burners Dimension - mm	Ø 70
External dimensions, Height:	250 mm
External dimensions, Width:	400 mm
External dimensions, Depth:	850 mm
Net weight:	38 kg

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2016.09.26