Electrolux

Modular Cooking Range Line thermaline 80 - 4 Zone Induction Top, 2 Sides

ITEM #

MODEL #

NAME #

SIS #

AIA #



Modular Cooking Range Line

thermaline 80 - 4 Zone Induction Top, 2 Sides

588024 (MAIDACHOAO) Induction top, 4 zones, two-side operated

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top. Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304). 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Smooth glass ceramic surface without any "dead" spots allows for quick and easy cleaning. Features 9 power levels with fast deployment to full heating power and very low heat dissipation to the kitchen. Overheat protection switches off the supply in case of overheating. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.
IPX5 water resistance certification.
Configuration: Two-side operated top with backsplash. The base needs to be supplied by the factory. Please include appropriate base.

Main Features

- Almost the entire surface of the ceramic plate can be used without "dead" spots.
- Fast deployment with full heating power immediately.
- Low heat dissipation to the kitchen.
- Overheat protection: a temperature sensor switches off the supply in case of overheating.
- Pans can easily be moved from one area to another without lifting.
- The smooth glass-ceramic surface can be quickly and easily cleaned, thus providing maximum hygiene.
- IPX5 water resistance certification.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic silicon "soft" grip for easier handling and cleaning. The special design of the controls prevent infiltration of liquids or soil into vital components.
- 9 power levels.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.

Construction

- Control light for each zone.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top.
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.

APPROVAL:

Electrolux
Modular Cooking Range Line
thermaline 80 - 4 Zone Induction Top, 2 Sides

Optional Accessories

• Scraper for cook tops	PNC 910601 ❑
• Connecting rail kit, 800mm	PNC 912500 ❑
• Portioning shelf, 800mm width	PNC 912526 ❑
• Portioning shelf, 800mm width	PNC 912556 ❑
• Folding shelf, 300x800mm	PNC 912577 ❑
• Folding shelf, 400x800mm	PNC 912578 ❑
• Fixed side shelf, 200x800mm	PNC 912583 ❑
• Fixed side shelf, 300x800mm	PNC 912584 ❑
• Fixed side shelf, 400x800mm	PNC 912585 ❑
• Connecting rail kit: modular 80 (on the left) to ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic (on the right)	PNC 912971 ❑
• Connecting rail kit: modular 80 (on the right) to ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic (on the left)	PNC 912972 ❑
• Endrail kit, flush-fitting, left	PNC 913109 ❑
• Endrail kit, flush-fitting, right	PNC 913110 ❑
• Endrail kit (12.5mm) for thermaline 80 units, left	PNC 913200 ❑
• Endrail kit (12.5mm) for thermaline 80 units, right	PNC 913201 ❑
• Insert profile D=800mm	PNC 913230 ❑
• Endrail kit, (12.5mm), for back-to-back installation, left	PNC 913249 ❑
• Endrail kit, (12.5mm), for back-to-back installation, right	PNC 913250 ❑
• Endrail kit, flush-fitting, for back-to-back installation, left	PNC 913253 ❑
• Endrail kit, flush-fitting, for back-to-back installation, right	PNC 913254 ❑

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2016.09.26

Modular Cooking Range Line thermaline 80 - 4 Zone Induction Top, 2 Sides

Front



Top



EI = Electrical connection
EQ = Equipotential screw

Side



Electric

Supply voltage:	
588024 (MAIDACHOAO)	400 V/3N ph/50/60 Hz
Total Watts:	20 kW

Key Information:

Configuration:	Two-Side Operated;Top
Front Plates Power:	5 - 5 kW
Back Plates Power:	5 - 5 kW
Front Plates dimensions:	320x330 320x330
Back Plates dimensions:	320x330 320x330
Induction Top Dimensions (width):	800 mm
Induction Top Dimensions (depth):	800 mm
External dimensions, Height:	250 mm
External dimensions, Width:	800 mm
External dimensions, Depth:	800 mm
Net weight:	44 kg

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2016.09.26