Electrolux

Modular Cooking Range Line thermaline 85 - Full Module Gas Fry Top with Mixed Plate, 1 Side with Backsplash

ITEM #

MODEL #

NAME #

SIS #

AIA #



Modular Cooking Range Line

thermaline 85 - Full Module Gas Fry Top with Mixed Plate, 1 Side with Backsplash

588541 (MBHOBBHOPO)	Gas fry top with smooth and ribbed chrome plate, one-side operated with backsplash

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top. Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304). 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Smooth/ribbed chromium-plated mild steel cooking surface with non-stick finishing for optimal grilling. Stainless steel high splash guards on the rear and sides. Features safety thermostat, thermostatic control and led indication of pilot flame. Electrical ignition powered by battery with thermocouple for added safety. Large drain hole enables draining of cooking juices into a large collector. Overheat protection switches off the supply in case of overheating. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.
IPX4 water resistant certification.
Configuration: One side operated top with backsplash. The base needs to be supplied by the factory. Please include appropriate base.

APPROVAL:

Main Features

- Choice of one or two heating zones. An indicator lamp shows operating state of each zone.
- Large drain hole on cooking surface permits the draining of residual cooking juices into a large collector placed under the cooking surface.
- Overheat protection: a temperature sensor switches off the supply in case of overheating.
- Stainless steel high splash guards on the rear and sides of cooking surface.
- Units have separate controls for each half module of the cooking surface.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic silicon "soft" grip for easier handling and cleaning. The special design of the controls prevent infiltration of liquids or soil into vital components.
- Safety thermostat and thermostatic control.
- IPX4 water resistance certification.
- Electrical ignition powered by battery with thermocouple for added safety.
- Led indication of pilot flame

Construction

- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in 2 mm and 3 mm in 1.4301 (AISI 304).
- Cooking surface in chromium-plated mild steel with non-stick finishing for optimum grilling results.
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top.
- Cooking surface to be 2/3 smooth and 1/3 ribbed.

Electrolux

Modular Cooking Range Line
thermaline 85 - Full Module Gas Fry Top with Mixed Plate, 1 Side with Backsplash


Optional Accessories

- Connecting rail kit for appliances with backsplash, 850mm — PNC 912498 ❑
- Portioning shelf, 800mm width — PNC 912526 ❑
- Portioning shelf, 800mm width — PNC 912556 ❑
- Folding shelf, 300x850mm — PNC 912579 ❑
- Folding shelf, 400x850mm — PNC 912580 ❑
- Fixed side shelf, 200x850mm — PNC 912586 ❑
- Fixed side shelf, 300x850mm — PNC 912587 ❑
- Fixed side shelf, 400x850mm — PNC 912588 ❑
- Connecting rail kit for appliances with backsplash, right — PNC 912979 ❑
- Connecting rail kit for appliances with backsplash, left — PNC 912980 ❑
- Back panel, 800x700mm, for tops and units with backsplash — PNC 913013 ❑
- Endrail kit, flush-fitting, with backsplash, left — PNC 913115 ❑
- Endrail kit, flush-fitting, with backsplash, right — PNC 913116 ❑
- Scraper for smooth plates — PNC 913119 ❑
- Scraper for ribbed plates — PNC 913120 ❑
- Endrail kit (12mm) for thermaline 85 units with backsplash, left — PNC 913206 ❑
- Endrail kit (12mm) for thermaline 85 units with backsplash, right — PNC 913207 ❑
- U-clamping rail for back-to-back installations with backsplash — PNC 913226 ❑


The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Modular Cooking Range Line
thermaline 85 - Full Module Gas Fry Top with Mixed Plate, 1 Side with Backsplash

Front




Top



EQ = Equipotential screw
G = Gas connection

Side



Gas

Gas Power:	
588541 (MBHOBBHOPO)	68180 Btu/hr (20 kW)
Gas Type Option:	
Gas Inlet:	1/2"

Key Information

Configuration:	One-Side Operated;Top
Cooking Surface Depth:	615 mm
Cooking Surface Width:	700 mm
Working Temperature MIN:	110 °C
Working Temperature MAX:	270 °C
External dimensions, Height	250 mm
External dimensions, Width	800 mm
External dimensions, Depth	850 mm
Net weight:	120 kg
Cooking surface type:	2/3 Smooth 1/3 Ribbed
Cooking surface - material	Chromium Plated

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.