
HENKOVAC
QUALITY VACUUM SYSTEMS

SEAL CONFIGURATIONS M4, M5 & M6



MOBILE M4, M5, M6


M4 options:







M5 options:









M6 options:







SPECIFICATIONS M4, M5 & M6

STAINLESS STEEL COVER & FLAT WORKING SURFACE

	SEAL LENGTH			MAX. PRODUCT HEIGHT	USEFUL CHAMBER SIZE (WXDXH)	OUTSIDE DIMENSION (WXDXH)	STANDARD VOLTAGE*	POWER CONSUMPTION	WEIGHT
	L	S&S	L&S						
M4	620	2 x 520		200	max. 620 x 505 x 200 (L)	735 x 900 x 1130 (1470**)	400-3-50 Hz	3,3 kW	180 kg
M5	2 x 820	2 x 620	780 x 520	210	max. 805 x 605 x 200 (LS)	935 x 1000 x 1140 (1540**)	400-3-50 Hz	3,5 kW	240 kg
M6	2 x 1020	2 x 620	980 x 520	210	max. 1005 x 605 x 200 (LS)	1135 x 1000 x 1140 (1540**)	400-3-50 Hz	3,5 kW	280 kg

*Dimensions in mm *Machines can be supplied with all world wide voltages applicable **Open cover requires more space*

OPTIONS M4, M5 & M6

	DIGITAL TIME CONTROL	SENSOR CONTROL	SEAL	SEAL CONFIGURATION	GAS	PUMP CAPACITY M^3	CYCLE TIME
M4	10 programs	sensor/H_2O	Double/CC/CCC/2S***	L S&S	gas	40 or 63 m^3	20-40 sec
M5	10 programs	sensor/H_2O	Double/CC/CCC/2S	L&L S&S L&S	gas	63 or 100 m^3	25-35 sec
M6**	10 programs	sensor/H_2O	Double/CC/CCC/2S	L&L S&S L&S	gas	100 m^3	25-35 sec

*Model M6 standard coverheight 210 mm, optional cover 260 mm height ***CC = Clean Cut, CCC = Clean Cut Controlled, 2S = Two Sides*