WASHING

HIGH SPIN WASHERS
LOW AND MEDIUM CAPACITY
LA-35C/45C TP2



CHARACTERISTICS

TP2
- User friendly and totally programmable 7".
- USB Connection. Online platform free of charge for programming, telemetry, data analysis… thanks to the IoT.
- Videos on display (ads, instructions).
- 37 languages.
- 8 dosing signals as standard.

G FACTOR
- High G-Factor: G-FACTOR 450.

EFFICIENCY
- Intelligent consumption.
- Optimal loading.
- Water Recovery tanks ready: KRS.
- Low water consumption.

VERSATILITY
- Make to order: customisation.
- OPL < > COIN.
- Electric < > Hot water.
- Drain valve < > Pump.
- Wet cleaning features.

CONNECTIVITY
- IoT - FagorKonnect standard.
- Remote technical service.
- Managemant of laundries: OPL and COIN.
- Remote payment.

ERGONOMICS
- Biggest door diameters: Ø560.
- Easy opening/closing system for door lock.

MAINTENANCE
- Hinged control panel: easy and ergonomic access.
- Technical menu: statistics for technicians and maintenance with external console (with console option).

OTHERS
- Grey skinplate outer casing.
- Drum and tub in stainless steel AISI 304.
- Detergent dispenser with 4 compartments.
- Electronic control of imbalance with frequency control.
- LOADING AID system: water and rotation control.
- CB and WRAS approved product. Option ETL.
- High spin washers with suspended drum.

OPTIONS

- DQ-2 Dosing pump kit.
- Extra dosing pump DB-1.
- Double drain.
- Normally closed valve.
- Water FULL FLOW: recirculation of bath water.
- Levelling feet.
- Auto Weight: automatic weighing sensor system on feet (Includes kit with 6 extra dosing signals).
- Relay card with 6 extra dosing signals: up to 14 signals.
- Reversible door opening.
- Tropicalized model: protected board.
- Steam kit to transform an E or HW heated machine into steam version.
- Plinth to align loading height (door base at 850mm).
- Stainless steel AISI 304 outer casing.
- Stainless steel AISI 304 front panel (LA-35C).
- Maritime voltage for electric models: 440V III 50/60 Hz.
- No neutral.
- Voltage 230 V III 50/60 Hz.
- Coin/token kit.
- Auto unlock kit for the door.

	U.	LA-35C TP2		LA-45C TP2	
DRUM					
Load capacity 1:9 / 1:10	Kg	39/35		47/42	
Volume	l	350		450	
Diameter	mm	860		860	
Depth	mm	602		720	
GENERAL DETAILS					
Washing speed / Spining speed	r.p.m.	42,5/966		42,5/966	
G Factor	-	450		450	
Maximum force transmitted	KN	7,36 ±2,45		7,36 ±2,45	
Frequency-dynamic force	Hz	14,3		14,3	
Sound level	dB	<70		<70	
Coin laundry version	-	Yes		No	
Double drain	-	Opt.		Opt.	
Weighing System / Tilting System	-	Opt./No		Opt./No	
SLUICE option	-	No		No	
DOOR					
Height center door / Height door	mm	885/540		885/540	
Diameter	mm	560		560	
POWER					
Motor	kW	6		6	
Electric heating power	kW	21		21	
Total electric power (electric model)	kW	22		22	
Total electric power (hw, steam model)	kW	6		6	
CONNECTIONS		ELECTRIC	STEAM/HOT WATER	ELECTRIC	STEAM/HOT WATER
Tension 230V - III + T	Nº x mm2 / A	3x16+T / 63A	3x4+T / 32A	3x16+T / 63A	3x4+T / 32A
Tension 400V - III + N + T	Nº x mm2 / A	4x6+T / 40A	4x1,5+T / 16A	4x6+T / 40A	4x1,5+T / 16A
Steam inlet (Steam mod.)	inch	3/4"		3/4"	
Maximum steam consumption (Steam mod.)	Kg/h	18		18	
Water inlet	inch	3/4"		3/4"	
Water main pressure	Kg/cm^2	2-4		2-4	
Maximum water consumption	Lit/h	261,3*		335,9*	
Drain	mm/inch	3"		3"	
Drainage capacity	Lit/min	200		200	
DIMENSIONS / PACKING DIMENSIONS					
Net Width / Gross Width	mm	1.095/1.205		1.095/1.205	
Net Depth / Gross Depth	mm	1.184/1.330		1.304/1.440	
Net Height / Gross Height	mm	1.730/1.850		1.730/1.850	
Net weight / Gross weight	Kg	735/786		747/853	
Volume	m^3	2,7		3,3	

* Programme No. 20, 75% load



01. Soap dispenser
02. Emergency stop
03. USB port
04. Drain
05. Electric connection to liquid soap pump
06. Electrical connection
07. Main switch
08. Auxiliar water inlet
09. Hot water inlet
10. Equipotential connection
11. Cold water inlet
12. Blur output / Water overload
13. Liquid soap connection
14. Steam connection
15. Ethernet port

		A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	CGY	CGZ
LA-35C	mm	1.095	1.184	1.730	525	560	158	576	1.330	1.498	1.331	1.513	1.417	61	74	101	596	676	976	808	384	1.028	946	1.496	740	1.558	795	732
LA-45C	mm	1.095	1.304	1.730	525	560	158	576	1.330	1.498	1.331	1.513	1.417	61	74	101	596	676	976	808	384	1.028	946	1.496	740	1.558	795	800